

TURBOPLUG

Cement Based, Set in 3-4 Seconds, Shock Setting Water Plug

Description

Cement-based, reinforced with special additives and polymers, ready to use powder waterproofing plug that stops running water through holes or cracks in concrete or masonry within 3-4 seconds.

Fields of Application

- On masonry or cement based surfaces.
- Waterproofing of active water leak.
- To block water leak before waterproofing.

Features and Benefits

- Ready to apply.
- Stops water leaks due to the fast setting property.
- Resistant to corrosion.
- Topcoat insulation material can be applied within a short time after application.

Technical Data

Content	Mix of mineral fillers and special cement
Color	Grey
Mixing	Ready to use
Application Temperature	+5°C to +25°C
Set Time	3-4 seconds
HS Code	3824.99.70.00.00

Application Procedure

Preparation of Substrate

The application surface must be clear, durable and clean off any dirt, dust, paint, mud, etc. that may prevent the product from sticking on the surface. The cavities, cracks, or the leakage points from which the active water leakage occurs must be opened up to the solid ground. The surface must be wetted before the application.

TURBOPLUG

Cement Based, Set in 3-4 Seconds, Shock Setting Water Plug

Application Method

Powder formed TURBOPLUG is placed in the palm of your hand and pressed on active water leakage. Waiting constantly until product hardens and water flow stops.

Consumption

2 kg powder product for 1 lt leakage.

Packaging

5 kg plastic bucket

Shelf Life

6 months in original, unopened package.

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with water immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

- Pre-dampen the substrates prior to placing **WATERSHOCK**.
- Do not use as a surface-applied coating or as a pargeting material.
- It may be harmful with skin contact.
- Wear protective gloves during the application
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +5°C and above +25°C.

TURBOPLUG

Cement Based, Set in 3-4 Seconds, Shock Setting Water Plug

Health and Safety

Warning! Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.