

ROAD FL 223

Asphalt Paint

Description

BAUMERK ROAD FL 223 is a two component asphalt paint with acrylic polymer based special cement polymer modified.

Fields of Application

It can be suitable on old and new asphalts.

Features and Benefits

- Excellent adhesion performance.
- Does not show fading, cracking, blistering and spilling.
- Non odour.
- Dirt free.
- Does not show discoloration within time.
- Provides 3 times more durability in comparison with normal asphalt surfaces.
- Resistant to UV light and atmospheric conditions.
- Provides waterproofing.

Technical Data

Content	Acrylic Resin
Thinning	Ready to use
Recommended Coat	2 coats
Application Tools	Brush / Spray
Drying Time	
<i>First curing</i>	<i>15 minutes</i>
<i>Waiting period between the coats</i>	<i>2 hours</i>
<i>Full curing</i>	<i>24 hours</i>
GTIP No	3208.90.91.00.23

ROAD FL 223

Asphalt Paint

Application Procedure

Preparation of Substrate

Application surfaces should be clean off the rust, dirt and moisture. Surface should be clean and dry.

Application Method

Powder form A component is added in liquid B Component package slowly, after 1.5 liter water added under 400-500 rpm mixer and mix 3-5 minutes until homogenous mixture obtained. Paint should be applied with 110 PSI air compressor spray gun on asphalt as one or two coats. In brush application, paint should be applied until no any black color remains on asphalt surface.

Consumption

1,0-1,4 kg/m²

Packaging

A component: 16,5 kg + B component:6,5 kg = 23 kg set

Shelf Life

12 months in original, unopened package.

Storage

Store in dry area between +5°C and +35°C. Protect from heat, freezing and direct sunlight.

Cleanup Information

Clean tools and equipment with industrial type solvents immediately after use. Dried material can only be removed mechanically.

Cautions / Limitations

ROAD FL 223

Asphalt Paint

- Ensure the curing of the paint before set into operation of the system and increase the temperature slowly.
- It may be harmful with skin contact.
- Do not apply in freezing conditions or during precipitation.
- Protect applied materials from rain, freezing, foot traffic and continuous high humidity until completely dry.
- Do not use when air and surface temperatures are below +3°C and above +35°C.

Health and Safety

Warning! Cause eye and skin irritation. If eye or skin contact, get immediate medical attention. If swallowed, do not induce vomiting. Call a physician or poison control center. Never give anything by mouth to an unconscious person.

Wash hands thoroughly after handling. Wear protective clothing, gloves, eye and face protection. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Dispose of unused, contents, container and other contaminated wastes in accordance with local, state, federal and provincial regulations.

Keep container closed when not in use. Keep out of the reach of children.

Limited Warranty: This product is subject to a written limited warranty which can be obtained free of charge from BAUMERK Company. Please contact with technical service department for further information and support.